

■ 标准品一览表 Standard size

静电容量 Cap(uF)	Outline size (mm)		ESR @1KHZ (mΩ)	Ls (nH)	Î (A)	Irms @40°C/10KHZ (A)	Part number
	ΦD (mm)	H (mm)					
Un: 350V.DC							
20	38	40	3.3	25	1200	30	C45206****□2UE*70○
30	45	“	3.2	“	1800	40	C45306****□2UE*70○
30	38	50	“	“	1500	30	C45306****□2UG*70○
40	45	“	3.0	“	2000	35	C45406****□2UG*70○
50	49	“	“	“	2500	40	C45506****□2UG*70○
60	54	“	“	“	3000	45	C45606****□2UG*70○
70	58	“	“	“	3500	50	C45706****□2UG*70○
80	55	60	“	“	3200	50	C45806****□2UI*70○
100	61	“	2.9	“	4000	55	C45107****□2UI*70○
Un: 700V.DC							
20	38	40	3.3	25	1200	30	C45206****□26E*70○
30	45	“	3.2	“	1800	40	C45306****□26E*70○
30	38	50	“	“	1500	30	C45306****□26G*70○
40	45	“	3.0	“	2000	35	C45406****□26G*70○
50	49	“	“	“	2500	40	C45506****□26G*70○
60	54	“	“	“	3000	45	C45606****□26G*70○
70	58	“	“	“	3500	50	C45706****□26G*70○
80	55	60	“	“	3200	50	C45806****□26I*70○
100	61	“	2.9	“	4000	55	C45107****□26I*70○
Un: 800V.DC							
20	44	40	2.9	25	1200	40	C45206****□28E*70○
30	54	“	2.7	“	2400	45	C45306****□28E*70○
30	45	50	2.6	“	1800	40	C45306****□28G*70○
30	40	60	2.8	“	1500	35	C45306****□28I*70○
40	62	40	2.5	“	3200	55	C45406****□28E*70○
40	52	50	2.7	“	2400	45	C45406****□28G*70○
40	46	60	3.2	“	2400	40	C45406****□28I*70○
50	69	40	2.1	“	4000	60	C45506****□28E*70○
50	59	50	2.4	“	3000	50	C45506****□28G*70○
50	52	60	2.5	“	3000	45	C45506****□28I*70○
60	64	50	2.3	“	3600	55	C45606****□28G*70○
60	56	60	2.4	“	3600	50	C45606****□28I*70○
70	70	50	2.0	“	4200	60	C45706****□28G*70○
70	62	60	2.2	“	4200	55	C45706****□28I*70○
80	73	50	2.1	“	4800	60	C45806****□28G*70○
80	65	60	2.5	“	4800	60	C45806****□28I*70○
100	82	50	1.8	“	6000	75	C45107****□28G*70○
100	72	60	2.2	“	5000	65	C45107****□28I*70○

◇ 备注：特殊需要可根据客户要求另行设计

◇ Note: Special requirements can be designed according to customer requirements

■ 标准品一览表 Standard size

静电容量 Cap(uF)	Outline size (mm)		ESR @1KHZ (mΩ)	Ls (nH)	Î (A)	I _{rms} @40°C/10KHZ (A)	Part number
	ΦD (mm)	H (mm)					
Un: 1100V.DC							
10	42	40	3.4	25	600	35	C45106****□3BE*70○
20	50	50	3.1	“	1200	40	C45206****□3BG*70○
20	65	40	3.0	“	“	60	C45206****□3BE*70○
30	60	50	3.1	“	1800	55	C45306****□3BG*70○
40	69	“	2.7	“	2400	60	C45406****□3BG*70○
40	61	60	2.9	“	2000	55	C45406****□3BI*70○
50	68	“	2.6	“	2500	60	C45506****□3BI*70○
60	75	“	2.2	“	3000	70	C45606****□3BI*70○
70	81	“	1.9	“	3500	“	C45706****□3BI*70○
80	86	“	1.6	“	4000	75	C45806****□3BI*70○

- ◇ 备注：特殊需要可根据客户要求另行设计
- ◇ Note: Special requirements can be designed according to customer requirements
- ◇ 1.“****”表示内部特征码；“****”=Internal use
- ◇ 2.“□”表示容量偏差；“□”= Capacitance tolerance
- ◇ 3.“*”表示引出端型体；“*”= Specifications of terminals
- ◇ 4.“○”表示安装形式；“○”= Fix style