

■ 标准品一览表 Standard size

静电容量 Cap(uF)	Outline size (mm)			P ±0.5	P1 ±0.5	d ±0.5	Î (A)	I _{max} 70°C@10kHz (A)	ESR @10kHz (mΩ)	Ls (nH)	Part number
	W	H	T								
Urms: 350V. AC, Un=480V. AC, Undc=600V. DC											
0.33	32.0	18.0	9.0	27.5	----	0.8	17	1.6	53.9	17	C74334**H*□U2CA00
0.39	“	“	“	“	----	“	20	1.7	46.0	“	C74394**H*□U2CA00
0.47	“	“	“	“	----	“	24	1.9	38.6	“	C74474**H*□U2CA00
0.68	“	20.0	11.0	“	----	“	35	2.5	27.5	18	C74684**H*□U2CA00
0.82	“	22.0	13.0	“	----	“	42	3.0	23.3	“	C74824**H*□U2CA00
1.0	“	“	“	“	----	“	51	3.2	19.6	“	C74105**H*□U2CA00
1.5	“	24.5	15.0	“	----	“	76	4.2	14.0	19	C74155**H*□U2CA00
2.0	“	30.0	16.0	“	----	“	102	5.0	11.1	21	C74205**H*□U2CA00
2.2	“	“	“	“	----	“	112	5.2	10.4	20	C74225**H*□U2CA00
2.5	“	“	18.0	“	----	1.0	127	6.2	7.0	22	C74255**H*□U2CA00
3.0	“	37.0	22.0	“	----	“	153	7.4	5.8	24	C74305**H*□U2CA00
3.3	“	“	“	“	----	“	168	7.7	5.3	“	C74335**H*□U2CA00
3.5	“	“	“	“	----	“	178	7.9	5.0	23	C74355**H*□U2CA00
4.0	“	“	“	“	----	“	204	8.2	4.4	“	C74405**H*□U2CA00
1.0	41.0	22.0	11.0	37.5	----	“	36	2.8	28.0	24	C74105**J*□U24A00
1.5	“	24.0	13.0	“	----	“	55	3.7	19.3	25	C74155**J*□U24A00
2.0	“	26.0	15.0	“	----	“	73	4.6	14.9	26	C74205**J*□U24A00
2.2	“	“	“	“	----	“	80	4.8	13.7	25	C74225**J*□U24A00
2.5	“	30.0	16.0	“	----	“	91	5.3	12.3	27	C74255**J*□U24A00
3.0	“	“	“	“	----	“	109	5.7	10.5	26	C74305**J*□U24A00
3.3	“	32.0	17.0	“	----	“	120	6.2	9.7	29	C74335**J*□U24A00
3.5	“	“	“	“	----	“	128	6.4	9.3	28	C74355**J*□U24A00
4.0	“	33.5	18.5	“	----	“	146	7.0	8.3	29	C74405**J*□U24A00
4.5	“	37.0	22.0	“	----	“	164	8.0	7.6	31	C74455**J*□U24A00
5.0	“	“	“	“	----	“	182	8.3	7.0	30	C74505**J*□U24A00
5.5	“	“	“	“	----	“	201	8.6	6.6	29	C74555**J*□U24A00
6.0	“	41.0	26.0	“	----	“	219	9.7	6.2	32	C74605**J*□U24A00
6.5	“	“	“	“	----	“	237	10.0	5.8	31	C74655**J*□U24A00
7.0	“	“	“	“	----	“	255	10.3	5.5	“	C74705**J*□U24A00
7.5	“	“	“	“	----	“	274	10.5	5.3	30	C74755**J*□U24A00
8.0	“	“	“	“	----	“	292	“	5.1	“	C74805**J*□U24A00
8.5	“	43.0	28.0	“	----	“	310	“	4.9	32	C74855**J*□U24A00
9.0	“	“	“	“	----	“	328	“	4.7	31	C74905**J*□U24A00
9.5	“	45.0	30.0	“	----	“	347	“	4.5	33	C74955**J*□U24A00
10.0	“	“	“	“	----	“	365	“	4.4	32	C74106**J*□U24A00

◇ 备注：特殊需要可根据客户要求另行设计

◇ Note: Special requirements can be designed according to customer requirements

■ 标准品一览表 Standard size

静电容量 Cap(uF)	Outline size (mm)			P ±0.5	P1 ±0.5	d ±0.5	İ (A)	I _{max} 70°C@10kHz (A)	ESR @10kHz (mΩ)	Ls (nH)	Part number
	W	H	T								
Urms: 350V. AC, Un=480V. AC, Undc=600V. DC											
10.0	57.0	45.0	25.0	52.5	----	1.2	260	11.6	5.7	34	C74106**M*□U25A00
11.0	“	“	“	“	----	“	286	11.9	5.3	33	C74116**M*□U25A00
12.0	“	“	29.5	“	20.3	“	312	14.1	4.4	29	C74126**M*□U25H00
5.0	“	“	35.0	“	“	“	391	16.4	3.7	31	C74505**M*□U25H00
16.0	“	“	“	“	“	“	417	16.8	3.5	30	C74166**M*□U25H00
18.0	“	50.0	“	“	“	“	469	18.1	3.2	33	C74186**M*□U25H00
20.0	“	“	40.0	“	“	“	521	19.	2.9	32	C74206**M*□U25H00
21.0	“	“	“	“	“	“	547	20.1	2.8	32	C74216**M*□U25H00
25.0	“	55.0	45.0	“	“	“	651	22.8	2.5	34	C74256**M*□U25H00
27.0	“	“	“	“	“	“	703	23.5	2.4	33	C74276**M*□U25H00

- ◇ 备注：特殊需要可根据客户要求另行设计
- ◇ Note: Special requirements can be designed according to customer requirements
- ◇ 1.“**”、“*”表示内部特征码；“**”、“*”=Internal use
- ◇ 2.“□”表示容量偏差；“□”= Capacitance tolerance